

# PARTNER

CARE . TRUST . RESPONSIBILITY

## All in One POS Terminal PT-6315



### All in one POS Terminal PT-6315 Features

- Celeron 1.8GHz Dual Core, Elegant, compact fanless design
- Integrated Triple track MSR
- Integrated 80mm Thermal Printer, Choice of Front Paper out of Rear Paper out
- 2x20 VFD Customer display, Choice of integrated Customer Display 2x20 VFD or 7" LCD (Option)
- Design with easy cable management
- WLAN, RFID (optional)
- Integrated Dual Display(Optional)

# High Performance Fanless All in one POS Terminal

Partner Tech is pleased to announce next generation of high performance All-in-One POS terminal PT-6315.

PT-6315 embedded with powerful Intel Celeron 1.8GHz Dual Core processor yet fanless design, brings the power to run today's power hunger POS applications.

PT-6315 is not only the solution for small and medium business, the all in one design with ease cable management brings the mobility capability that can fit in with any environment installation.

Its an affordable yet easy to use integrated terminal, which can help small and medium business to serve customer effectively, and keep pace with competitors.

The compact base embedded with 80mm thermal printer, touch screen and integrated customer display, design with attractive appearance and small footprint for counter space saving.

Item	PT-6315
CPU	Intel® Processor Celeron 1.8GHz dual core fanless design
Chipset	Intel chipset
LCD	15" LCD, resolution 1024 x 768 LED backlight LCD
Touch	5 wire resistive touch screen
Construction	Plastic cover & metal heat sink bottom
Memory	2G up to 16G (DDR3)
Ethernet	Onboard 10/100/1000 BASE-T Gigabit Ethernet
Storage	Internal 2.5" type SATA HDD (optional SATA SSD)
External I/O Interface	4 * COM ports [COM1~4 on rear I/O (COM1~2 powered with DC+0/5/12V, BIOS selection; COM3~4 by Jumper setting) 1 * DB-15 VGA port 1 * DB-25 for LPT port 1 * RJ11 port supports 2 cash drawer(DC+24V) 1 * RJ-45 LAN port with activity and link LEDs 4 * USB 2.0 1 * PS2 Keyboard port 1 * DC +12V input power-jack for adapter
Printer	Front paper out 80mm 180 DPI 180mm/s or Rear Paper out 80mm 203 DPI 250mm/s
MSR	3 tracks magnetic reader
Optional	Customer display module (2 x 20 VFD) or Dual display Pole CD-70 or Pole Display RFID WLAN
Operation System	POS Ready 2009, POS Ready7, Windows XP, Windows 7, Windows 8.1 Industry Pro Retail, Linux (Ubuntu)
Power Supply	AC100~240V/DC12V, 15A, 180W adapter
Operating Temp	0°C ~ +40°C
Certification	CE, FCC, LVD, VCCI, BSMI, 3C



15" TFT LCD Touch Screen



Integrated Dual Display with Adjustable Pole (option)



Integrated 2 x 20 VFD Integrated 7" LCD (option)



Rear Paper out printer



Front Paper out printer

\* specification subject to change without prior notice



CARE . TRUST . RESPONSIBILITY

## Partner Tech Corporation

Taiwan (HQ) TEL:+886-2-29188500 FAX:+886-2-29153405 E-mail:sales@partner.com.tw

USA E-mail:sales@partnertechcorp.com

Europe E-mail:info@partner-tech.eu

UK E-mail:sales@partnertechuk.com

China E-mail:sales@partnertech.com.cn

Korea E-mail:adams\_c@partner.com.tw

South Africa E-mail:sales@partnertech.co.za

North Africa E-mail:sales@partnertechna.com

Middle East E-mail:sales@partnertechme.com

Australia E-mail:sales@partner-tech.com.au

