ТОИСН

SATURN All-IN-ONE



CPU

Intel Celeron Quad Core J1900 up to 2.42Ghz

Touch Display Options

- 8.4" Projected Capacitive Touch
- •12.1" True Flat Resistive Touch

Integrated Options

- 3 Track MSR (12")
- Magtek EMV / MSR Combo (8")
- Digital Persona Fingerprint Reader
- Internal Wireless a/b/g/n/ac/ Bluetooth

The Saturn AIO features the Intel® Celeron® Quad Core J1900 2.0 GHz is available in both an 8.4" and 12.1"and is a completey fanless design, making it amenable to all size and space requirements

Capable of Gigabit connectivity and a PCIe expansion board for wireless and 2nd Gigabit LAN, this unit is outstanding for its operability. Standard with VGA, LAN and COM Ports, coupled with multiple base and mounting options, its ease of maintenance will give your business the opportunity to break limits in expandability and flexibility.



Saturn All-In-One

TOUCH DYNAMIC

| _ | | |
|--|--|--|
| Processor | Saturn All In One 8.4" | Saturn All In One 12.1" |
| CDU | Intel®Celeron®Quad Core J1900 up to 2.42 Gnz | Intel [®] Celeron [®] Quad Core J1900 up to 2.42 Ghz |
| CPU Cara Logia | SOC (System on Chin) | COC (System on Chin) |
| Core Logic | SOC (System-on-Chip) | SOC (System-on-Chip) 1x DDR3L so-DIMM 4GB up to 8GB, 1333 Mhz |
| System Memory | 1x DDR3L so-DIMM 4GB up to 8GB, 1333 Mhz | · · · · · · |
| Graphics | Intel HD Graphics with Dx11 Support | Intel HD Graphics with Dx11 Support |
| LCD Display | | |
| LCD | 8.4" LED LCD | 12.1" LED LCD |
| Touch | True Flat Projected Capacitive | True Flat Resisitive |
| Brightness | 380 NITS (LED LCD) | 500 NITS (LED LCD) |
| Maximum Resolution | 800x600 | 1024x768 |
| Backlight Type | LED | LED |
| Thermal Solution | | |
| Fanless | Yes | Yes |
| Storage | | |
| Hard Drive | N/A | 1x2.5" SATA HDD |
| SSD | 1x2.5" SATA SSD | 1x2.5" SATA SSD (optional) |
| Rear I/O Ports | | |
| USB | 4 x USB 2.0, 1 x USB 3.0 | 4 x USB 2.0, 1 x USB 3.0 |
| VGA | 1 D-SUB15 | 1 D-SUB15 |
| Speakers | 2x2 Watts | 2x2 Watts |
| LAN | Gigabit LAN controller 10/100/1000 | Gigabit LAN controller 10/100/1000 |
| 2nd LAN | Optional | Optional |
| | COM x3 (COM1. COM2 standard, COM3 with | COM x3 (COM1. COM2 standard, COM3 with |
| COM | +5V/ +12V Power) | +5V/ +12V Power) |
| Input Power | DC Jack with Locking Connector | DC Jack with Locking Connector |
| Cash Drawer | 1 | 1 |
| Power Switch | 1 | 1 |
| PS2 | N/A | Optional |
| Expansion | | |
| | PCle for wireless LAN or 2nd Gigabit NIC | PCIe for wireless LAN or 2nd Gigabit NIC |
| Slot | Expansion | Expansion |
| Peripherals | | |
| MSR | Magtek Edynamo MSR/EMV | Integrated ID Tech 3 Track MSR |
| Fingerprint Reader | Digital Persona (optional) | Digital Persona (optional) |
| Internal | | |
| Wireless/Bluetooth | a/b/g/n/ac (optional) | a/b/g/n/ac (optional) |
| Multiple Base Options | Triangle, Desktop, Universal Printer Base | Triangle, Desktop, Universal Printer Base |
| Technical Specs | | |
| Specs | 9.75" x 7.5" x 2" | 12.75" x 9.75" x 2.25" |
| Power Adapter | 19V, 65W | 19V, 65W |
| IP Rating | IP54 Front Rating | IP54 Front Rating |
| OS Support | | |
| 8.4" & 12.1" | Windows 7 Pro, Pos Ready 7, Windows 8.1 Pro, Windows 8.1 Embedded Industry Retail Pro, | |
| | Windows 10 IOT, Windows 10 Pro, Linux | |
| 64 Bit Support | Yes | Yes |
| 888.508.6824 sales@touchdynamic.com www.touchdynamic.com | | |