



Features

- True flat color TFT LCD display
- Optimal display resolution 800 x 480
- Ventless design
- Light weight
- VESA 75 x 75mm wall mount standard
- Adjustable tilt/turn angle

LV3000

LCD Pole Display

The LV3000 is a true flat LCD customer display with compact and ecological design. The power consumption is only 2.5W with LED backlight. It has the ability to deliver multi-media messages and transaction information at the same time.



LV3000 SPECIFICATIONS

LCD MONITOR

Color	Black
Display size	7in (17.78cm)
Active area	6in x 3.4in (15.24cm x 8.6cm)
Optimal resolution	800 x 480 (WVGA)
Brightness	200 cd/m ² (typ)
Contrast ratio	500:1 (typ)
Response time	25 ms (typ)
LCD viewing angle	140° (H) / 110° (V)
Tilt angle	70° (H) / 35° (V)
Input signal connector	USB Type B
Input frequency	Horizontal: 31.5 - 60.2 kHz Vertical: 56.3Hz - 75Hz

ELECTRICAL

Power consumption	500mA/2.5W
Power supply	DC 5V +/- 5%

ENVIRONMENT

Temperature	Operating: 32°F to 104°F (0°C to 40°C) Storage: 14°F to 122°F (-10°C to 50°C)
Humidity	Operating: 20% to 80% Storage: 10% to 90%

MECHANICAL

Weight	2.6 lbs (1.17 Kg)
Wall mount	VESA 2.9in x 2.9in (7.3cm x 7.3cm)
Stand base	3in pole + 7in pole + base (7.6cm + 17.78cm + base)
Dimensions (H x W x D)	19in x 7.5in x 4.2in (48.2cm x 19.05cm x 10.6cm)