Epson TM-H6000IV (024): Serial, w/o PS, EDG, MICR, E/P



DATASHEET















Building on the success of the TM-H6000III, this printer features improved power efficiency and reduced paper usage to help lower your overheads. Administrators will appreciate the new remote management feature, easy installation and two interfaces onboard.

Use less paper

Shrink paper usage by up to 31 percent with the TM-H6000IV's paper save feature. Instead of squeezing logos and text, which causes distortion and can compromise legibility, the 'paper save' feature automatically reduces blank spaces and barcode height. It also prints the top of the next receipt before cutting the current one to decrease the top margin.

Use less power

Lower utility overheads with ENERGY STAR-qualified power efficiency.

Save time and hassle

Easily manage a fleet of TM-H6000IV printers over a network using the new remote management feature. Monitor every printer's status and usage from a single location, and carry out settings changes remotely.

Simple integration

Get the freedom to switch to a USB environment at any time, with USB included as standard in addition to the changeable second interface.

Eye-catching greyscale graphics

Make a good impression on customers with high-quality receipts. The TM-H6000IV delivers eye-catching greyscale logos and graphics, ideal for reinforcing branding or communicating special offers more effectively.

Speedy transactions

Every transaction is fast and fuss-free with the TM-H6000IV's improved print speeds of up to 300mm/sec for receipts and 5.7 lines per second for slips. To ensure customers are not frustrated by cheque processing failures, the optional MICR reader has an accuracy rate of over 99 percent.

KEY FEATURES



PRODUCT SPECIFICATIONS

FONTS & STYLES

Print Speed receipt 300 mm/sec

Print Speed slip 5.70 lps (40 columns, 17.80 cpi)
Print Speed endorsement 4.00 lps (40 columns, 21.20 cpi)

Column capacity slip 45 cps / 60 cps Column capacity endorsement40 cps

Character size receipt 1.41 mm (W) x 3.39 mm (H) \prime 0.99 mm (W) x 2.4 mm (H) Character size slip 1.56 mm (W) x 3.11 mm (H) \prime 1.24 mm (W) x 3.11 mm (H)

Character size endorsement 1.09 mm (W) x 2.41 mm (H)

INTERFACES

Interfaces RS-232, USB 2.0 Type B, Drawer kick-out, Customer Display

POWER

Power Supply PS-180 (option)

GENERAL

Product dimensions 186 x 278 x 181 mm (Width x Depth x Height)

Product weight 4.4 kg
Color Epson Dark Gray
Noise Level Operation: 55 dB (A)

RECEIPT SLIP / F/P Print method Thermal line printing 9-pin serial impact dot matrix 9-pin serial impact dot matrix Print speed 300 mm/sec 5.70 lps (40 columns, 17.80 cpi) 4.00 lps (40 columns, 21.20 cpi) **FONTS & STYLES** Column capacity 45 cps / 60 cps 40 cps Character size 1.41 mm (W) x 3.39 mm (H) / 0.99 mm (W) x 1.56 mm (W) x 3.11 mm (H) / 1.24 mm (W) x 2.4 mm (H) 3.11 mm (H) 1.09 mm (W) x 2.41 mm (H)

OTHER

Warranty 24 months Carry in

Optional warranty extension available

LOGISTICS INFORMATION

SKU	C31CB25024
EAN code	8715946486734
Dimensions Single Carton	300 x 400 x 300 mm
Carton Weight	5.8 Kg
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	56 Units (8 x 7)
Pallet Size Block	63 Units (9 x 7)

Epson TM-H6000IV (024): Serial, w/o PS, EDG, MICR, E/P

WHAT'S IN THE BOX

- Main unit
- Thermal roll paper
- Ribbon cartridge (slip)
- Power switch cover
- Connector Cover
- User manual

SUPPLIES

 Epson ERC32B Ribbon Cartridge for TM-U675/-H6000 series, M-U420/820/825, black C43S015371

OPTIONAL ACCESSORIES

- Epson PS-180
 C32C825341
- Epson UB-E02 C32C824151
- Epson UB-P02II C32C823891
- Epson UB-S01 C32C823361
- Epson UB-R03 C32C824461
- Epson UB-S09 C32C823861
- Epson UB-U01III C32C824111
- Epson UB-U02III
 C32C824121
- Epson UB-U03II
 C32C824131



For more information please contact:

Telephone: 01952 607111 (UK)+ 01 436 7742 (Republic of Ireland) E-mail: enquiries@epson.co.uk Chat: etalk.epson-europe.com Fax: 0871 222 6740 + Local call rate. Web: www.epson.co.uk www.epson.ie

